



SAFETY DATA SHEET

1. Identification

Product Identifier	P.O.G.	
Other means of identification		
Product code	BP-3452	
Recommended use	Paint, oil, and grease remover.	
Recommended restrictions	Professional use only.	
Manufacturer/supplier/distributor/importer information		
Company name	BonnetPro	
Address	4529 Bethlehem Pike Telford, PA 18969	
Telephone	1-877-477-1615 or 215-872-7138	
Emergency phone number	PERS	(800) 633-8253
	24 hour Emergency	(800) 633-8253

2. Hazard(s) Identification

Physical hazards	Flammable Liquids	Category 4
Health hazards	Acute toxicity, oral	Category 5
	Skin irritant	Category 2
	Eye damage	Category 1
	Aspiration Hazard	Category 1

Environmental hazards Not classified.

OSHA defined hazards None

Label elements



Signal word	Danger.
Hazard statement	Combustible liquid. May be harmful if swallowed. Causes skin irritation. Causes serious eye irritation. May be fatal if swallowed and enters airways.

Precautionary statement

Prevention	Keep away from flames and hot surfaces. No smoking. Wear protective gloves/eye protection/face protection. Wash hands and exposed skin thoroughly after handling.
Response	In case of fire: Use water fog, foam or carbon dioxide (CO ₂) to extinguish. Call a POISON CENTER/doctor/medical professional if you feel unwell. IF ON SKIN: Wash with plenty soap and water for 15 minutes. Specific treatment (see section 4 on the Safety Data Sheet). If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor/medical professional. IF SWALLOWED: Immediately call a POISON CENTER/doctor/medical professional. Do NOT induce vomiting.
Storage	Store in a well-ventilated place. Keep cool. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None.

Supplemental information None

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Pentyl acetate	628-63-7	30-50
Alcohols, C9-11, ethoxylated	68439-46-3	20-30
C9-C15 Cycloalkanes	Mixture	10-20
C9-C15 Alkanes	Mixture	10-20
2-butoxyethanol	111-76-2	1-10
Other components below reportable levels		1-20

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.
Eye contact	Rinse with water for at least 15 minutes. Remove contact lenses if present and easy to do so. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur. Only induce vomiting at the instruction of medical personnel.
Most important symptoms/effects, acute and delayed	Dermatitis. Rash. May cause an allergic skin reaction.
Indication of immediate medical attention and special treatment needed	Provide general support measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to the hospital. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Carbon dioxide (CO ₂). Dry chemical powder, sand, or earth may be used for small fires only.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source or ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protecting clothing must be worn in case of fire.
Fire-fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapors or mists. Ensure adequate ventilation. Remove all sources of ignition. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
--	--

Methods and materials for containment and cleaning up

Eliminate all ignition sources. Use only non-sparking tools. Take precautionary measures against static discharge. Keep combustibles away from spilled material.

Large spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small spills: Absorb with earth, sand, or other non-combustible material and transfer to container for later disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original container for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Avoid discharge into areas not consistent with package labeling.

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Do not smoke. Use explosion proof equipment and non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Ground/bond container and equipment. Store in original tightly closed container. Store away from incompatible materials (see section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
2-butoxyethanol	PEL	50 ppm

US ACGIH Threshold Limit Values

Components	Type	Value
2-butoxyethanol	STEL	20 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Species	Sampling Time
2-butoxyethanol	200 mg/g	Creatinine	Urine	End of shift.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits.

Individual protection measures, such as personal protective equipment

Eye/face protection Avoid contact with eyes. Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke or use chewing tobacco. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical State	Clear liquid.
Color	Light yellow.
Odor	Characteristic.
Odor threshold	Not available.
pH	Not applicable.
Melting/freezing point	Not available.
Initial boiling point and boiling range	300-410°F (148.9-210°C) estimated.
Flash point	150°F (66°C) estimated.
Evaporation rate	Not available.
Flammability	Not available.
Flammability Limits	
Upper	6% estimated.
Lower	0.8% estimated.
Vapor pressure	Not available.
Vapor density	Not available.
Specific gravity (water=1)	0.90
Solubility in water	Insoluble.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.

10. Stability and reactivity

Reactivity	This product is stable and non-reactive under normal conditions of use.
Chemical stability	Material is stable under normal conditions. Store in a cool dark place.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Oxidizing agents, acids.
Hazardous decomposition products	Carbon dioxide, carbon monoxide.

11. Toxicological information

Information on likely routes of exposure

Ingestion	Expected to be low ingestion hazard.
Inhalation	Prolonged inhalation may be harmful.
Skin contact	May cause skin irritation.
Eye contact	Causes serious eye damage. Wear eye/face protection.

Symptoms related to the physical, chemical and toxicological characteristics Dermatitis. Rash.

Acute toxicity May be harmful if swallowed.

Product	Route and Species	LD ₅₀
P.O.G. (CAS mixture)		
Acute	<i>Oral, rat</i>	2,500 mg/kg estimated

*Estimates for product may be based on additional component data not shown

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation Causes serious eye damage.

Respiratory sensitization Not available.

Skin sensitization Not available.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity This product is not expected to be a carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)
Not Listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity – single exposure Not classified.

Specific target organ toxicity – repeated exposure Not classified.

Aspiration hazard May be harmful or fatal if product enters airways.

12. Ecological information

Ecotoxicity		
Product	Species	Test Results
P.O.G. (CAS mixture)		
Aquatic		
Fish	Fathead minnow	LC ₅₀ = 23 mg/L estimated
Crustacea	Daphnia Magna	EC ₅₀ = 14 mg/L estimated

*Estimates for product may be based on additional component data not shown

Persistence and degradability No data available.

Bioaccumulative potential Potential to bioaccumulation is expected to be low.

Mobility in soil No data available.

Other adverse effects Harmful to aquatic life. May cause long lasting harmful effects to aquatic life.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues/unused product Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner. (see: Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may contain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

15. Regulatory information

US federal regulations

SARA 302 Extremely hazardous substance

Not listed.

SARA 304 Emergency release notification

Not listed.

SARA 311/312 Hazard Categories

Immediate Hazard - Yes

Delayed Hazard – No

Fire Hazard – Yes

Pressure Hazard – No

Reactivity Hazard – No

SARA 313 (TRI reporting)

2-butoxyethanol (Glycol Ether Category)

16. Other information, including date of preparation or last revision

Issue date 1/6/2016

Revision date 1/6/2016

Version # 1

HMIS® ratings Health: 2
Flammability: 2
Physical hazard: 0

NFPA ratings Health: 2
Flammability: 2
Instability: 0

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge, and have been obtained from resources believed to be reliable. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered a warranty or quality specification. The information related only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified by the text.

Revision information First issue